

Convenient Feature

- Wide touch pad screen
- User-friendly accessibility







Key Tag Mechanical Override Keys

Keypad volume control

Volume adjustable (3 levels including mute)

• 9V battery back-up

When batteries are discharged, put 9V battery to back-up power.

Low battery warning signal

A beep sound during door access will alert you to replace batteries.







Powerful Security

Random security code feature

User access code will be pressed after pressing two random numbers, preventing intruders from checking the fingerprint marks left.



2 random numbers appear before entering user access code



Press the user access code



Impossible to guess user access code due to random fingerprint marks



Automatic locking

The automatic locking feature eliminates the need to re-check for the door lock when you go out. Feel at ease when you go out and keep your home safe.



Double authentication

The double authentication mode strengthens security. User access code plus card must be authenticated to open the door(Optional).



Anti-theft mode

When leaving, the user can set up the anti-theft mode by simply pressing the button, preventing tampering by creating a warning sound.





Specification

Model	SHS-H505
RFID	ISO 14443A type (13.56Mhz)
User Access Code	4~12 digit number combination
RFID Card/ Password	Capacity 31(max.)
Material	Zn, Al, ABS
Humidity	20~80%
Temperature	-20°C ~ +60°C
Size(WxHxD)mm	Exterior Body: 81 X 302 X 66 Interior Body: 79 X 290 X 80
Door Thickness	AML220:40~60mm AML320:61~80mm
Power	DC 6V (AA Alkaline batteries) x8pcs
Battery Life	Approximately 18 months (Average -10 times per day)
Lockset	Mortise type